NeoLine COMPOSITES

DATA SHEET

Composite Fluted Siding

Depth, texture and architectural shadow lines.

For feature walls, entrances, soffits and accent areas in contemporary exterior designs.

PRODUCT SPECIFICATIONS

Profile	Fluted / dimensional
Nominal length	9.5 ft (approx. 2,896 mm)
Nominal width	8.7 in (approx. 221 mm)
Nominal thickness	1 in (25.4 mm)
Effective coverage	6.2 sq ft / board (approx. 0.576 m²)
Material	Wood-plastic composite
Protective cap	Co-extruded Surlyn™ resin
Surface	Brushed finish
Connection	Interlocking tongue and groove
Fastening	Concealed, factory pre-drilled slots
Slot spacing	Every ¾ in (approx. 19.1 mm)
Residential warranty	25-year limited material warranty



RECYCLED COMPOSITE CORE

65% recycled wood fibres · 30% recycled high-density plastic · 5% adhesive

Recycled wood and plastic account for 95% of the stated core ingredients.

INSTALLATION & CARE

- Interlocking boards fasten directly to metal furring or wood strips with self-tapping screws; no separate clips are required.
- Pre-drilled slots allow natural movement when correctly fastened. Follow the installation guide for fasteners, clearances and fixing details.
- No regular painting or staining. Clean according to the product care guidance.

COLOUR OPTIONS

- Pebble Beige
- Golden Oak
- Honey Oak
- Misty Grey
- Graphite
- Onyx Black
- Dark Walnut
- Desert Sage