DECKTILES / PRODUCT OVERVIEW

NeoLine Composite DeckTiles

Ready-made modular outdoor flooring with a capped composite surface and an integrated aluminum frame. Built for strength, easy placement and individual tile access.

READY-MADE MODULE

Capped boards + integrated aluminum base

White Oak shown. Product image not to scale.

INSTALLED TILE LAYOUT

A repeatable grid. A tailored outdoor finish.

Alternating tile orientations shown.

TILE FOOTPRINT

1.9 x 1.9 ft

Approx. 580 x 580 mm

TOTAL PROFILE

2 in

50.8 mm overall height

WEIGHT PER TILE

7.2 kg

Approx. 15.87 lb

NOMINAL COVERAGE

3.61 sq ft

Approx. 0.34 m2 per tile

DIY-friendly. Built for lasting outdoor use.

1. **LESS CONVENTIONAL CONSTRUCTION**
   Ready-made panels simplify placement on a suitable prepared base.
2. **RIGID, ROT-PROOF ALUMINUM BASE**
   An integrated frame supports the composite surface and helps retain alignment.
3. **LIFT-UP ACCESS + LOW MAINTENANCE**
   Lift modules to access the surface below. No routine staining, sanding or sealing.

info@neolinecomposites.com 604-716-6661

VIEW PRODUCT WEBPAGE

Scan or click to explore

TYPICAL APPLICATIONS

Patios and balconies | rooftop terraces | concrete overlays | commercial amenity areas

Application suitability depends on the substrate, drainage, loading and project design.

PRODUCT SPECIFICATION

Technical data + project planning

Nominal product values for planning and estimating. Confirm the assembly details and current installation requirements before specifying or ordering.

CRITERION	PRODUCT DATA
Tile dimensions	1.9 ft x 1.9 ft (approximately 580 x 580 mm).
Overall tile height	2 in (50.8 mm), aluminum-frame base to composite surface. Excludes pedestals and protective or levelling layers.
Nominal weight	7.2 kg (15.87 lb) per complete tile.
Nominal coverage	3.61 sq ft (approximately 0.34 m2) per tile. Round estimates up to whole tiles and allow for layout cuts and waste.
Integrated substructure	Structural-grade extruded aluminum framing.
Walking surface	Capped NeoLine composite decking boards with a brushed finish.
Installation options	Modular floating placement on suitable flat, stable and drained surfaces; compatible NeoLine adjustable-pedestal layouts where specified.
Care + maintenance	Routine cleaning and debris removal. No routine sanding, staining or sealing. Follow current product care instructions.
Material warranty	25-year residential / 10-year commercial material coverage, subject to eligibility, exclusions and current written terms. Do not assume identical coverage for every support component.

Colours + finishes

White Oak



Misty Grey

Honey Oak



Graphite



Desert Sage

Dark Walnut

Product images are indicative. Colour and grain vary by screen and production batch; approve a physical sample.

Project coordination

1. **SUBSTRATE + WATERPROOFING**
   Verify base condition, drainage paths, membrane compatibility and protection.
2. **LAYOUT + EDGE DETAILS**
   Coordinate movement, door clearances, perimeters and any required restraint.
3. **SUPPORT + SITE CONDITIONS**
   Use the specified pedestal layout; confirm roof capacity, loads and wind uplift.
4. **DIY + PROJECT REVIEW**
   Simple sites may suit DIY placement. Complex or code-regulated sites need qualified review.

PRODUCT DATA NOTICE This sheet is not a structural load, span, fire or slip-resistance certification. Tile weight alone does not establish wind-uplift compliance. DeckTiles are not a waterproofing membrane.

Product details + enquiries

Compatible subframe systems